

DEVILBISS®

Conventional

**A GIFT FROM WEIGHTLESS
OUTER SPACE**



APOLLO SPACE GUN **eco**

Magnesium Gun Body

394g

**Super Light Weight
High Transfer Efficiency Spray Gun**

CARLISLE
FLUID TECHNOLOGIES

SUPER LIGHT WEIGHT SPRAY GUN WITH THE MOST GENTLE ON EARTH'S ENVIRONMENT

• Super Light Weight

The world first magnesium gun body has allowed to produce a super light weight spray gun at 394g.

• Finest Atomization

You can select an air cap from the wide range of DeVilbiss's JGA air caps renowned as finest atomization quality.

• Anodized Aluminum Fluid Passage

The fluid passage is made of Anodized Aluminum, compatible with all types of paints including waterborne. (less-weight compared with Stainless steel)

• PTFE Coated Gun Body

Preventing from stains on the gun body and for easy cleaning, PTFE coated gun body is employed.

Selection of Air Cap, Fluid Tip and Gun Type

■ For your ordering reference:

APOLLO-C – Air cap No. – Tip Size – S : Suction type
G : Gravity type
P : Pressure type

(Example) : **APOLLO-C – 704 – FX – P**

Air Inlet	: G 1/4
Fluid Inlet	: G 3/8 (Gravity Feed : G 1/4)
Air Inlet Pressure	: 0.69 MPa (max)
Fluid Inlet Pressure	: 0.69 MPa (max)
Gun Body	: Magnesium
Fluid Passage	: Anodized Aluminum Insert Stainless steel Nozzle & Needle
Weight	: 394 g (with 777 air cap)

■ Specifications

Air Cap	Pattern Rang (mm)	Type	Air Consumption ℓ /min (MPa)	Tip Size (mm)									Compressor (kW)	Applications
				0.7 G	1.1 FX	1.4 FF	1.4 FV	1.6 FW	1.8 EE	1.8 EX	1.8 E	2.2 D		
43	300	S/G	291 (0.28)	—	—	○	—	—	—	○	—	—	2.2~3.7	Auto refinishing, Metallic
64	360	P	386 (0.28)	—	—	—	—	—	—	—	—	○	2.2~3.7	Heavy body, Procelain glazes
67	360	P	462 (0.35)	—	—	—	—	—	○	—	○	—	2.2~3.7	Procelain glazes
186	340	S/G	274 (0.28)	—	—	—	○	○	—	○	—	—	2.2~3.7	Auto refinishing, Metallic
704	230	P	230 (0.28)	○	○	○	—	—	—	—	○	—	2.2~3.7	General
705	230	P	347 (0.28)	○	○	○	—	—	—	—	—	—	2.2~3.7	General
765	360	P	412 (0.35)	—	○	○	—	—	—	—	○	—	2.2~3.7	General, Fine refinishing
777	360	P	487 (0.35)	—	○*	○	—	—	—	—	○	—	2.2~3.7	Automotive, Metallic, Adhesive
797	330	P	493 (0.35)	—	○	○	—	—	—	—	○	—	2.2~3.7	Automotive, Metallic
799	360	P	493 (0.35)	—	○	○	—	—	—	—	—	—	2.2~3.7	Automotive, Metallic

→ G: Gravity type / S: Suction type / P: Pressure type

* Soft seat tip version (APOLLO-C-777-FX-P-T) also available for APOLLO-C-777-FX-P

■ Accessories

• KGL-400	Gravity Cup (400ml, Anodized Aluminum) G 1/4	• KGP-4	Gravity Cup (400ml, resin) G 1/4
• KGL-400-FA-ST	Gravity Cup (400ml, Anodized Aluminum Free Angle) G 1/4	• KR-470-1C	Suction Cup (700ml, Aluminum) G 3/8
• KG-400C	Gravity Cup (400ml, Stainless Steel) G 1/4	• HAV-501-B	Air Inlet Control Valve and Gauge
• KG-400T	Gravity Cup (400ml, PTFE-coated) G 1/4	• HAF-507	Disposable Air Filter
• KG-250	Gravity Cup (250ml, Stainless Steel) G 1/4	• SSL-10	Spray Gun Lube (60ml)

※ For improvement purposes, Design & Specifications may change without prior notice.

DEVILBISS

CFT RANSBURG JAPAN KK

15-5, Fukuura 1-chome, Kanazawa-ku, Yokohama, Kanagawa Japan 〒236-0004
TEL : +81-45-785-6434 / FAX : +81-45-785-6517

HP <http://www.carlisleleft.co.jp>

For more information, please contact: