

The gun of choice for touch-up, shading, edging and detail decorating, EGA/EGHV touch-up guns provide precise control for any type of delicate spray finishing applications. The guns feature a forefinger trigger to enhance operator control, and a long needle taper to make detail work easy.

- Equipped with stainless steel tip and needle
- Knurled knobs allow fine spray adjustments for fluid and pattern control
- Fluid delivery by attached suction feed or remote pressure feed cup
- Ideal for hours of fatigue-free precision painting

### **Ordering Information**

The EGA/EGHV touch-up gun is available with the following air cap and fluid tip set-up, factory-assembled for immediate delivery.

#### Part No.

EGA-503-390F EGHV-531-397E

#### EGA/EGHV Accessories

- 8 oz. Cup (TGS-503) Solvent-resistant polyethylene cup available
- Remote Cups Two-quart remote cups are available in aluminum (KB-555) or stainless steel (KB-545-SS)
- Additional Accessories Hose assemblies, air cap test kit, gun and hose cleaning equipment and other accessories also are available

# Technical Specifications - EGA

Body: Drop forged aluminum

Weight: 7 oz. (196 gr) with air cap and ring Air and Fluid Inlet 100 psi (7 bar) max., 1/4" NPS(M)

Wetted Parts: Aluminum Body

400-grade stainless steel Tip and Needle

Feed Type: Pressure and Siphon Feed

(Material Supply)

EGA/EGHV Touch-Up Spray Gun

Air Consumption: 3 CFM @ 30 psi Service Bulletin: SB-2-163 Repair Kit: KK-5044

# Technical Specifications – EGHV

Body: Drop forged aluminum Weight: 7.5 oz (210 gr)

Air and Fluid Inlet 100 psi (7 bar) max., 1/4" NPS(M)

Wetted Parts: Stainless Steel

Feed Type: Pressure and Siphon Feed

(Material Supply)


Air Consumption: 8.8 CFM @ 10 psi cap pressure
Air Cap Pressure: 10 psi @ 50 psi inlet

Service Bulletin: SB-2-167 Repair Kit: KK-5044


I-2179-A

# Refer to Service Bulletin: EGA - SB-2-163, EGHV - SB-2-167

# EGA/EGHV Touch-Up Spray Gun



# EGHV (HVLP)



# Parts List EGA (Conventional)

Ref. No.	Model No.	Description	Ind. Parts Required		
1	EGA-4	Packing Nut	1		
<b>2</b>	38273-136-K5	Fluid Needle Packing (Kit of 5)	1		
3	EGA-7	Baffle	1		
4	EGA-4000-F	Tip, Needle and Gasket (lapped) (includes 4, 5, ● )	1		
<b>■</b> 5	EGA-59-K5	Gasket (Kit of 5)	1		
6	EGA-443	Trigger and Stud Assy.	1		
■ 7	AG-3-1-K5	Trigger Bearing Stud (Kit of 5)	1		
8	EGA-40-390	Air Cap	1		
9	EGA-11	Retaining Ring	1		
10	EGA-454	Fan Adjusting Assembly	1		
<b>■</b> 11	SSG-8205-K10	O-Ring (Kit of 10)	1		
<b>■</b> 12	AG-26-K10	Washer (Kit of 10)	2		
14	EGA-3	Packing Gland	1		
<b>■</b> 16	AG-7-K5	Needle Spring Kit (Kit of 5)	1		
17	AG-16	Fluid Needle Adjusting Screw	1		
18	EGA-441	Air Valve Assy.	1		
19	AG-46-K3	Lock Nut (Kit of 3)	1		
<b>2</b> 0	EGA-9-K5	Stem (Kit of 5)	1		
<b>2</b> 1	SST-3008-K5	Ball (Kit of 5)			
23	GD-36-K5	Spring Retainer (Kit of 5)			
<b>2</b> 4	EGA-5-K6	Air Valve Plunger (Kit of 6)			

<sup>■</sup> A quantity of necessary parts is included in Gun Repair Kit KK-5044. Suffixes -K3, -K5, etc. designates kits of multiple parts. Example 38273-136-K5 is a kit of (5) packings.

#### Parts List EGHV (HVLP)

Ref. No.	Model No.	Description	Ind. Parts Required	
1	EGA-4	Packing Nut	1	
<b>2</b>	38273-136-K5	Needle Packing (Kit of 5)	1	
3	EGHV-439-397HV	Air Cap with Ring	1	
4	EGA-7	Baffle (air distributor)	1	
5	EGA-4000-E	Tip, Needle and Gasket Assy. (lapped) (includes 5, 6, ● )	1	
6	EGA-59-K5	Gasket (Kit of 5) (Polyethylene)	1	
7	EGA-443	Trigger and Stud Assy.	1	
■ 8	AG-3-1-K5	Trigger Bearing Stud (Kit of 5)	1	
<b>9</b>	EGA-5-K6	Air Valve Plunger (Kit of 6)	1	
10	EGA-454	Fan Adjustment Assy Horn	1	
<b>1</b> 1	SSG-8205-K10	O-Ring (Kit of 10)	1	
<b>1</b> 2	AG-26-K10	Washer (Kit of 10)		
14	EGA-3	Packing Gland		
<b>1</b> 6	AG-7-K5	Needle Spring (Kit of 5)	1	
17	AG-16	Needle Adj. Screw		
18	EGA-441	Air Valve Assy.		
19	AG-46-K3	Lock Nut (Kit of 3)		
<b>2</b> 0	EGA-9-K5	Stem (Kit of 5)		
<b>2</b> 1	SST-3008-K5	Ball (Kit of 5)		
23	GD-36-K5	Spring Retainer (Kit of 5)	1	
24	EGHV-3	Fluid Adapter	1	

<sup>■</sup> A quantity of necessary parts is included in Gun Repair Kit KK-5044. Suffixes -K3, -K5, etc. designates kits of multiple parts. Example: EGA-59-K5 is a kit of (5) seals.

# Air Cap Selection Guide

	Typical	Air Cap	Air Cap	Air Consumption @ 70°F		Typical Pattern Size	Fluid Tip No. and Size	Туре
Model	Materials	Model No.	Part No.	PSI	SCFM	in. (mm)	in. (mm)	of Feed ▶
EGA (Convention	Detail, Touch-Up, mal) Stains, Lacquer	390	EGA-40-390 ▲	30	3	Up to 3" (75)	F .042" (1.1)	P, S
EGHV	Detail, Touch-Up,	#397HV	EGHV-439-397HV	10	8.8	Up to 6" (150)	E .070" (1.8)	P, S

Type of Feed Reference: P = Pressure S = Suction

#### Air Cap Test Kit

KK-5043 Air Cap Test Kit - Includes air cap and gauge, for use with #397HV air caps only.

# Fluid Tips (Nozzles) & Needles

Model	# on Fluid Tip	Order Tip and Needle Set
EGA (Conventional)	F	EGA-4000-F
EGHV (HVLP)	Е	EGA-4000-E





<sup>▲</sup> Retaining Ring Required: Part No. EGA-11