DEVILBISS.

微粒化の良さで定評のあるJGXガンをベースに 高塗着を目指しLVMP化した・・・

LVMP for higher transfer efficiency by inheriting the Fine Atomization feature of JGX Gun well reputed



使いやすさ、高微粒化を追求したデビルビスの自補修専用スプレーガン

DeVILBISS offers an Easy-To-Operate, Fine Atomization spray gun for automotive refinishing







The JGX-502 air spray gun, an improved version of the JGX-501, is a product of the latest finishing technology developed in Japan, in cooperation with DEVILBISS in USA, a pioneer and current leader in the finishing industry for more than 120 years.

The JGX-502 air cap is retained onto the spray gun by a retaining ring that screws to threads on the baffle. The retaining ring is made from lightweight and very durable POM. This feature provides a longer gun life cycle and in the event of thread damage, only the replacement of the baffle is required.

Selection of Air Cap, Fluid Tip and Needle **Ordering Information** JGX-502 — Air Cap No. Fluid Tip Size - Feed Type G=Gravity S=Suction 103 / 143 / 165 GY / FX / FF / EX Basic Gun Model P=Pressure Example: JGX-502-143-FF-G

Air Cap No. (Color)	Feed Type	Fluid Tip Size (mm)				Air Pressure	Pattern	
		GY 0.8	FX 1.1	FF 1.4	EX 1.8	Air Consumption	Width (mm)	Characteristics
No. 103 (Red)	G (Gravity)	0			_	1.0 kg/cm² 80 ℓ /min.	100	For low fluid flow rates: Spot touch-up
	S (Suction)							
No. 143 (Silver)	G (Gravity)	_	0	0	0	2.0 kg/cm² 260 ℓ /min.	250	For medium to high fluid flow rates: Autorefinishing, general purpose, all finishes high atomization
	S (Suction)	_	_	0	0			
No. 165 (Blue)	P (Pressure)	_	0	0	_	3.0 kg/cm² 440 ℓ /min.	300	For medium to high fluid flow rates: High performance, general purpose, all finishes

Notice: The fluid tip of Suction Feed gun and GY Tip (0.8 mm) is not with soft-seat.

Accessories

• TLC-555 1 ℓ suction cup with PTFE coated inner lining • KG-400 400m ℓ gravity cap with stand (Stainless Steel)

 KG-400T 400m ℓ gravity cap with stand (PTFE coated)

• KB-555 2 \ell pressure feed remote cup • KR-470-1 700m ℓ suction cup (Aluminum)

• KG-250 250m ℓ gravity cap • HAV-501-B

Air control regulator-attaches at air inlet on gun handle

• HD-505-W Gun & Hose cleaner (5 ℓ)

• JGX-101 Repair Kit

• HAF-507 Disposable air line filter • SSL-10

Gun lube (60 m ℓ)

* For improvement purposes, Design & Specifications may change without prior notice.

FT RANSBURG JAPAN KK

15-5, Fukuura 1-chome, Kanazawa-ku, Yokohama, Kanagawa Japan 〒236-0004 TEL: +81-45-785-6434 / FAX: +81-45-785-6517

HP http://www.carlisleft.co.jp

For more information, please contact