
DEVILBISS

Air spray gun



■ For your ordering reference



Air cap	Part Number	Feed type	Tip size (Φ mm)
	LUNA2i-R-254-1.0-G	Gravity	1.0
	-1.3-G	Gravity	1.3
Cupar flat wide	-1.5-G Gravity		1.5
Super flat wide pattern	-1.8-G	Gravity	1.8
pattern	LUNA2i-R-254-1.3-S	Suction	1.3
	-1.5-S Suction		1.5
	-1.8-S	Suction	1.8
	LUNA2i-R-255-1.0-G	Gravity	1.0
	-1.3-G	Gravity	1.3
	-1.5-G	Gravity	1.5
High arched wide pattern	-1.8-G	Gravity	1.8
pattern	LUNA2i-R-255-1.3-S	Suction	1.3
	-1.5-S	Suction	1.5
	-1.8-S	Suction	1.8

Air cap

i series (newly developed)



Super thin-film flat wide pattern



PLS series







For Primers

High arched wide pattern

Improving operability and durability

Improving Operability No.1

♦ 1.5mm extension air valve



Delicate trigger control by increasing trigger

Improving Operability No.2

- ♦ Lower tangibility of needle spring
- ♦ Newly designed front seal

MMMMMMMM



Less load for trigger, 30% lower compared with our current product

Improving Durability

- ♦ Replaced to brass needle knob
- ♦ Lower tangibility of needle spring







screw thread

Lighten burden and increase durability for

Makeover

♦ Change color of some parts







Gravity cups & Accessories

Gravity cups



KGL-400-FA-ST (Free angle type)

Specifications Fluid connection: G1/4 Capacity · 400 cc Anodized aluminum



KG-400C-FA (Free angle type)

Specifications

Fluid connection : G1/4 Capacity : 400 cc Stainless steel



Air Valve (with gauge)





Multi-Lid

for 400cc gravity cup

DEVILBISS

LFT Ransburg Japan KK

15-5, Fukuura 1-chome, Kanazawa-ku, Yokohama, Kanagawa Japan 236-0004 TEL: +81-45-785-6434 / FAX: +81-45-785-6517

http://www.carlisleft.co.jp/

®DEVILBISS is a registered trademark of Carlisle Fluid Technologies. ®LUNA is a registered trademark of CFT Ransburg Japan KK.

For more information, please contact:

Air inlet : G1/4(M)

Air outlet : G1/4(F)

Weight






Superthfin-filmflat254




Decrease uneven finishing result by equable micro particles and wide pattern, realizing easily fine finishing result.





Gradual and low arched pattern allows you to realize fine finishing result with wet feeling by equable micro particles.



Atomization	Air cap No.	Tip size (Φ mm)		Pattern range (mm)	Delivery (ml/min)	Air consumption (I/min)	Air inlet (MPa)	Compressor (kw)	Weight (Gun only) (g)	Air inlet	Fluid inlet	Applications / Others
LVMP-Hi		1.0	G (Gravity)	260	80	191	0.15 2.2	2.2	265	G 1/4	4 G 1/4	Color clears Candy paint High-luminance metallics Fine finishing Medium to large workpiece
		1.3		280	120							
		1.5		295	132							
	254	1.8		310	155							
		1.3		280	120							
		1.5	- (295	132							
		1.8		310	155							
		1.0		260	78	182						
		1.3	G (Gravity)	290	119							
	255	1.5		300	130							
		1.8		320	155							
		1.3		290	119							
		1.5	S (Suction)	300	130							
		1.8		320	155							

* For improvement purposes, Design & Specifications may change without prior notice.

Measurement condition: one liquid high solids coating | Viscosity: 12 seconds | Air pressure for atomization: 0.15MPa | Turn fluid adjustment knob to fully open | Turn pattern valve to fully open | Distance: 200mm *There is a possibility of split spray pattern by fluid condition, atomization air pressure or pattern valve to fully open due to flat pattern behavior. Reduce air pressure by rotating pattern valve clockwise.



Intelligence Sharpen our technology



Stable finer atomization


Even finer renowned atomization

"LVMP-Hi" finer, flat and stable atomization technology

Realize equable particles by the stability made by the balance of air pressure and air volume. Thus it sprays fine particles flatly and widely.



Maintain wet feeling in spite of super thin-film flat with wide pattern



To cover High-luminance metallies and color clears application

Meet painters' wide-ranging demands

5 variations

We are aware of the increase of finishing required expertise such as color clear, candy, and high-luminance metallics i series are made with wide pattern and flat thin film for adapting these next technologies.

You can do now what you couldn't before, You can do easily now what you felt difficulty before.

